




Lyric4


0.4 cm³ coupler data

FRYE CIC coupler

Output sound pressure level



Acoustic gain




Frequency range	120 Hz - >10000 Hz			
Total harmonic distortion	500 Hz	800 Hz	1600 Hz	3200 Hz
	1.5%	1.0%	1.0%	1.0%
Equivalent input noise level	26.0 dB SPL			


2 cm³ coupler data

ANSI / ASA S3.22-2014
IEC 60118-0 : 2015

Output sound pressure level



Acoustic gain



Frequency range	140 Hz - >10000 Hz			
Total harmonic distortion	500 Hz	800 Hz	1600 Hz	3200 Hz
	1.5%	1.0%	1.0%	1.0%
Equivalent input noise level	30.0 dB SPL			

General test information

- All data obtained are measured with Phonak Target measurement settings
- The device is operating in linear mode
- The 0.4 cm³ coupler data is used as additional information which is closer to the real application, as the deep insertion leads to a significantly smaller residual volume in front of the ear drum

⚠ WARNING: Changes or modifications to the hearing aid that are not explicitly approved by Sonova AG are not permitted. Such changes may damage the ear or the hearing aid.



Sonova AG · Laubisrütistrasse 28
CH-8712 Stäfa · Switzerland

A Sonova brand

