Phonak Audéo™ L

Technical Data

Phonak Audéo L-R (L90/L70/L50/L30/L20/Trial)

S Receiver
2 cm^3 coupler data

ANSI / ASA S3.22-2014
IEC 60118-0 : 2015

Output sound pressure level

Maximum 111 dBSPL
HFA 106 dBSPL

Acoustic gain

Maximum 47 dB
HFA 40 dB

Frequency range	<100 Hz - >8000 Hz			
Total harmonic distortion	500 Hz	800 Hz	1600 Hz	3200 Hz
	1.5%	2.0%	2.0%	1.0%
Expected operating time*	18	h		
Equivalent input noise level	19	dBSPL		

M Receiver
2 cm^3 coupler data

ANSI / ASA S3.22-2014
IEC 60118-0 : 2015

Output sound pressure level

Maximum 114 dBSPL
HFA 111 dBSPL

Acoustic gain

Maximum 51 dB
HFA 46 dB

Frequency range	<100 Hz - >8000 Hz			
Total harmonic distortion	500 Hz	800 Hz	1600 Hz	3200 Hz
	1.5%	2.0%	2.0%	1.0%
Expected operating time*	18	h		
Equivalent input noise level	19	dBSPL		

General test information

- Specific measurement settings are used. RTS adjustment with volume control
- The device is operating in linear mode
- Low-level expansion is active
- All data obtained are measured with Phonak Target measurement settings

Warnings

⚠ This hearing instrument has an output sound pressure level that can exceed 132 dB SPL. Special care should be taken when fitting this instrument as there is a risk of impairing the residual hearing of the user.

⚠ Changes or modifications to the hearing aid that are not explicitly approved by the manufacturer are not permitted. Such changes may damage the ear or the hearing aid.

* Expected operating time of the rechargeable battery depends on active features, the use of wireless accessories, hearing loss, battery age and sound environment.

V1.00/2022-02/jas © 2022 Sonova AG All rights reserved/page 1/3

CE 0459
Sonova AG · Laubisrütistrasse 28
CH-8712 Stäfa · Switzerland
www.phonak.com

A Sonova brand

PHONAK life is on

Phonak Audéo™ L

Technical Data

Phonak Audéo L-R (L90/L70/L50/L30/L20/Trial)

MAV Receiver
2 cm^3 coupler data

ANSI / ASA S3.22-2014
IEC 60118-0 : 2015

Output sound pressure level

Maximum 119 dBSPL
HFA 117 dBSPL

Acoustic gain

Maximum 50 dB
HFA 46 dB

Frequency range	<100 Hz - >8000 Hz			
Total harmonic distortion	500 Hz	800 Hz	1600 Hz	3200 Hz
	1.5%	1.5%	1.0%	1.0%
Expected operating time*	18	h		
Equivalent input noise level	19	dBSPL		

P Receiver
2 cm^3 coupler data

ANSI / ASA S3.22-2014
IEC 60118-0 : 2015

Output sound pressure level

Maximum 122 dBSPL
HFA 120 dBSPL

Acoustic gain

Maximum 59 dB
HFA 56 dB

Frequency range	<100 Hz - 6300 Hz			
Total harmonic distortion	500 Hz	800 Hz	1600 Hz	3200 Hz
	1.0%	1.5%	1.0%	1.0%
Expected operating time*	18	h		
Equivalent input noise level	19	dBSPL		

* Expected operating time of the rechargeable battery depends on active features, the use of wireless accessories, hearing loss, battery age and sound environment.

V1.00/2022-02/jas © 2022 Sonova AG All rights reserved/page 2/3

CE 0459
Sonova AG · Laubisrütistrasse 28
CH-8712 Stäfa · Switzerland
www.phonak.com

A Sonova brand

PHONAK life is on

Phonak Audéo L-R (L90/L70/L50/L30/L20/Trial)

UP Receiver
2 cm^3 coupler data

ANSI / ASA S3.22-2014
IEC 60118-0 : 2015

Output sound pressure level

Maximum 132 dBSPL
HFA 124 dBSPL

Acoustic gain

Maximum 71 dB
HFA 65 dB

Frequency range	<100 Hz - 6100 Hz			
Total harmonic distortion	500 Hz	800 Hz	1600 Hz	3200 Hz
	1.5%	1.5%	1.0%	1.0%
Expected operating time*	18	h		
Equivalent input noise level	19	dBSPL		

* Expected operating time of the rechargeable battery depends on active features, the use of wireless accessories, hearing loss, battery age and sound environment.

V1.00/2022-02/jas © 2022 Sonova AG All rights reserved/page 3/3