




Standard Earhook HE11 2 cm³ coupler data

ANSI / ASA S3.22-2014 (R2020)
IEC 60118-0: 2022


Output sound pressure level




Standard Earhook HE11 680 2 cm³ coupler data

ANSI / ASA S3.22-2014 (R2020)
IEC 60118-0: 2022

Output sound pressure level




Acoustic gain




Frequency range	<100 Hz - >5000 Hz
Total harmonic distortion	500 Hz 2.0% 800 Hz 1.0% 1600 Hz 1.0% 3200 Hz 1.0%
Battery current	2.1 mA
Expected operating time*	133 h
Equivalent input noise level	19 dB SPL

Acoustic gain




Frequency range	<100 Hz - >5000 Hz
Total harmonic distortion	500 Hz 2.0% 800 Hz 1.0% 1600 Hz 1.0% 3200 Hz 1.0%
Battery current	2 mA
Expected operating time*	140 h
Equivalent input noise level	19 dB SPL

Induction coil sensitivity



Induction coil sensitivity



General test information

- Specific measurement settings are used. RTS adjustment with volume control
- The device is operating in linear mode
- Low-level expansion is active
- All data obtained are measured with Phonak Target measurement settings
- The latency of the audio signal determined according an internal standard is 6.2 ms

Warnings

- ⚠ This hearing instrument has an output sound pressure level that can exceed 132 dB SPL. Special care should be taken when fitting this instrument as there is a risk of impairing the residual hearing of the user.
- ⚠ Changes or modifications to the hearing aid that are not explicitly approved by the manufacturer are not permitted. Such changes may damage the ear or the hearing aid.

* Battery performance depends on active features, the use of wireless accessories, hearing loss, battery age, sound environment and earpiece. Note that for non-rechargeable ZnAir batteries operating time might vary depending on the battery model



Sonova AG · Laubisrütistrasse 28
CH-8712 Stäfa · Switzerland
www.phonak.com

A Sonova brand

