

SDS 3.0 Custom earpieces

Custom Hearing Instruments

Date: _____

Ordernr: _____

(Only for Phonak)

Step 1 - Order Details

Hearing center: _____

Contact / Phone: _____

Client Reference _____

Date of order: _____

Email address audiologist _____

Step 2 - Audiogram required for AOV


Left: HL dB

Right: HL dB

HL = hearing level 250 500 1000 2000 4000 Hz

Ear texture: Canallength:

- ☐ Soft
☐ Average
☐ Firm



Desired Canallength:

- ☐ Short
☐ Average (standard)
☐ Long
☐ Extra long

Step 3 - Select Custom Earpiece Style and Options

Please indicate Tube length 0-3 using the Phonak measurement tool

Left Right

		Receiver / tube type	SlimTube HE	Standard xReceiver (XS)	Power xReceiver (XP)	SuperPower xReceiver / UltraPower xReceiver (xSP plus) / (xUP)*	Shell color (Acryl/hard)	Transparent 21	Pink 26	Red 36/Blue 37	White 19
SlimTip Hard (hollow)	R ☐ L ☐							S			
SlimTip Hard (solid)	R ☐ L ☐							S			
cShell	R ☐ L ☐							S			
CROS Tip	R ☐ L ☐							S			

☐ standard ☐ not available

* Please specify hearing aid to check compatibility:



cShell & cShell XL



SlimTip Hard (hollow)



SlimTip Hard (solid)



Cros Tip

Faceplate color (cShell only): ☐ Pink 26 ☐ Tan 14 ☐ Cocoa 22 ☐ Transparent 13

Wax system (cShell and SlimTip XR): ☐ Cerustop ☐ Smartguard ☐ HF3 ☐ HF4

Vent size: ☒ AOV Audiogram required! ☐ Customer Specific: Left _____ mm Right _____ mm

Step 4 - Preference Service

If necessary, may we change the following? Yes No Call

Step down power level - if audiogram permits (maintain 6dB Gain Reserve) ☐ ☐ ☐

cShell can be build as half shell if required (build to cShell XL version) ☐ ☐ ☐

☐ Special instruction _____

Step 5 - Extra options

- ☐ Removal Cord ☐ Skeleton Lock
- ☐ Extend Removal Line +5mm transparent ☐ Canal Lock
- ☐ Helix Lock