

# Phonak Virto P Order Form

Phonak Virto P is the comprehensive ITE portfolio for mild to profound hearing losses. Virto P includes four models, four power levels, and four performance levels, including a noise generator for tinnitus management. Powered by the innovative technology of the Phonak Paradise platform, Virto P hearing aids are the ideal solution for those clients that prefer a custom-made solution with best hearing performance.

## Step 1: Order details

Account Number : \_\_\_\_\_

Hearing Clinic: \_\_\_\_\_

Delivery Address: \_\_\_\_\_

Contact Name: \_\_\_\_\_ Phone Number: \_\_\_\_\_

Email Address: \_\_\_\_\_

Date Ordered: \_\_\_\_\_ Date Required: \_\_\_\_\_

## Step 3: Warranty/VIP service

4th warranty (charges will apply)

VIP 24 hour service (\$57.75 incl GST)  
(VIP not available for Titanium products)

## Step 5: Product



Virto P-Titanium

L R

FitGuide values

L: \_\_\_\_\_ R: \_\_\_\_\_



Virto P-10 NW O

L R



Virto P-312 NW O

L R



Virto P-312

L R

## Step 6: Performance level

P90 P70 P50 P30

Note: Virto P Titanium models only available at 90 and 70 levels

## Step 7: Power level

Left M P SP UP\*

Right M P SP UP\*

\*UP only available with Virto P-312 models

## Step 8: Colours

### Shell

06 Black\*  
21 Transparent  
22 Cocoa  
26 Pink  
28 Brown  
R/B Red/Blue  
U0 Titanium gray\*\*

### Faceplate

06 Black\*\*\*  
22 Cocoa  
26 Pink  
28 Brown\*\*\*\*  
\* Only for Virto P-312  
\*\* Only for Virto P-Titanium  
\*\*\* Not for Virto P-312 NW O  
\*\*\*\* Brown faceplate not available for Virto P-Titanium

## Step 2: Patient information

Name: \_\_\_\_\_

Audiogram: (Required for Intellivent option)

	kHz	0.25	0.5	1	2	4
LEFT AC (dB HL)						
RIGHT AC (dB HL)						

## Step 4: Scanned impression information

Scan/Serial Number:	L		Phonak recommends new impressions for scanned images >12 months
	R		

## Step 9: Options

Fast order **▶▶** Build product as standard version





**Legend**  /  (S) = Standard  = Optional  
For selection options and codes see combination matrix on the back side.

Shell size	Smallest possible	<input checked="" type="checkbox"/> (S)
	Manually selected	Style:
Vent size	AOV (enter audiogram)	<input checked="" type="checkbox"/> (S)
	AOV-0 (Virto P-Titanium)	
	Manually selected	Left: mm Right: mm
Wax system	Cerustop (CS)	<input checked="" type="checkbox"/> (S)
	Manually selected	Type:
User controls	Standard controls	<input checked="" type="checkbox"/> (S)
	EasyPhone Et push button*	
	EasyPhone without push button*	
	MiniControl without push button*	
	Volume control (VC)*	
	T-coil*	
Removal line (RF)	Transparent (21)**	
	Line extension +5 mm (RFE)	
Titanium surface	Extra retention (ERS)	
Accessories (Virto P-312)	TV Connector	
	Phonak Partner Mic™	
	Phonak RemoteControl	

\*Not applicable for Virto P-312 \*\*Standard for IIC Et CIC

### Special Instructions

## Combination matrix

		Virto P-Titanium 	Virto P-10 NW O 	Virto P-312 NW O 	Virto P-312 
<b>Shell style</b>		IIC, CIC	IIC, CIC, ITC, HS, FS	ITC, HS, FS	HS, FS
<b>Push button</b>	Standard	No push button (PX)	Push button (PM1)	No push button (PX)	Push button (PM1)
	Optional	Push button (PM1)	No push button (PX)	Push button (PM1)	-
<b>Volume Control</b>	Standard	-	No VC (VCX)	No VC (VCX)	No VC (VCX)
	Optional	-	Digital VC (VC3)	Digital VC (VC3)	Digital VC (VC3)
<b>T-Coil</b>	Standard	No T-coil (TX)	No T-coil (TX)	No T-coil (TX)	-
	Optional	T-coil passive (TP)	T-coil passive (TP) (not available in combination with VC)	T-coil passive (TP) (not available in combination with VC)	-
<b>Magnetic switch function</b>	Standard	MiniControl (DT5)	EasyPhone (DT6)	EasyPhone (DT6)	-
	Optional	EasyPhone (DT6)	MiniControl (DT5) No magnetic switch (RX)	No magnetic switch (RX)	-
<b>Wax system</b>	Standard	Cerustop (CS)	Cerustop (CS)	Cerustop (CS)	Cerustop (CS)
	Optional	-	HF3 (H3) HF4 (H4) Extended rec. tube (ER) Wax Spring (WS) Ext. Tube + Spring (WE) Wax guard not required (X)	HF3 (H3) HF4 (H4) Extended rec. tube (ER) Wax Spring (WS) Ext. Tube + Spring (WE) Wax guard not required (X)	HF3 (H3) HF4 (H4) Extended rec. tube (ER) Wax Spring (WS) Ext. Tube + Spring (WE) Wax guard not required (X)
<b>Removal line</b>	Standard	Removal line transparent (RF)*	Removal line transparent (RF)*	-	-
	Optional	-	Removal line transparent (RF)	Removal line transparent (RF)	Removal line transparent (RF)

\* IIC & CIC will be standardly equipt with removal line

## Titanium information

### Vent Options

**AOV** = Acoustically Optimized Vent. Phonak will set the correct vent diameter and style in relation to Audiogram/shell geometry/feedback canceler and required low frequency gain. This is the recommended vent type.

**AOV-O** = Acoustically Optimized Vent-Open. This specific vent is more open and recommended for first time users and clients who are sensitive to occlusion.

### Titanium FitGuide

Measure the possible insertion depth. The device will be built in accordance with the indicated FitGuide value. If the measurement falls between two numbers, please use the smaller number.

- Side M - For devices with M-receiver
- Side P - For devices with P-receiver
- Models with SP receiver will be built without FitGuide information

### Impression Taking

Recommendation for taking deep impressions:

- Use EasyView Otablock **1**
- Provide deepest impression as possible **2**
- Always fill the complete concha with impression material **3**
- Intertragal notch must be visible **4**
- Impression length must cover the evaluated FitGuide value **5**

