Phonak Virto™ Marvel Order Form



Custom Hearing Instruments

Step 1: Customer Information Step 2: Patient Information Ship To Account: Last Name: Address: First Name: City: Gender: Age: State: Zip: Is this patient order being fully or partially paid for by state or federal Bill To Account: government funds? ☐ Yes ☐ No Third Party Patient Number: Audiogram (Required for AOV): Date: 250 500 3K HΖ 1K 2K 4K Purchase Order Number: Left: AC. Contact Name: ACRiaht: Phone Number: Email Address: Shipping & Handling Options* Next Morning (\$32.99) 2 Business Days (\$20.99) HI Warranty/Rush Options Next Afternoon (\$21.99) 3-5 Business Days (\$19.99) \bigcirc 2nd year \bigcirc 3rd year \bigcirc 4th year \bigcirc 24-hour service (\$64.99) * Based on location and courier Step 3: Product Step 7: Options Wireless (direct connectivity): For selection options and codes see combination matrix on the back side. Virto M-312 Legend /(S) = Standard= Optional Fast order Build product as standard version (Non-wireless: (S) Smallest possible Shell size Virto M-Titanium FitGuide values Manually selected Style: (L) (R) _ R:_ AOV (enter audiogram) (S) Virto M-10 NW 0 AOV-0 (Virto M-Titanium only) Vent size (L) (R) Left: Manually selected Right: Virto M-312 NW 0 Standard controls (S) (L) (R) Push button Step 4: Performance Level User controls Volume control (VC) Virto M-Titanium T-coil Other Virto M-10 NW 0/M-312 NW 0/M-312 (S) Cerustop (CS) Wax system M90 M70 M50 M30 Manually selected Type: Transparent (21)4 \bigcap^4 Removal line (RF) Step 5: Power Level Extra retention (ERS)/Matte Titanium surface M L R P L R SP (L) (R) UP¹ L R Acrylic/retention options See matrix for options Step 6: Colors TV Connector Shell **Faceplate** Phonak PartnerMic™ Black (06)1 Black (06)2 Accessories Phonak RemoteControl Transparent (21) Cocoa (22) (Virto M-312 only) Roger On™ iN Cocoa (22) Pink (26) Pink (26) (14) Roger Select™ iN Tan (14) Brown (28) Special Call me if changes are needed OK to make changes without phone call Instructions Brown (28) I would like to receive a paper user guide

Red/Blue (R/B)⁴
Titanium gray (U0)³

¹ Only available for Wireless Virto M-312

² Not available for Virto M-312 NW O

³ Only available for Virto M-Titanium

⁴ Standard for IIC and CIC

Combination matrix

		Virto M-Titanium	Virto M-10 NW 0	Virto M-312 NW 0	Virto M-312
Shell style		IIC, CIC	IIC, CIC, MC, C, HS, FS	MC, C, HS, FS	HS, FS
Push button	Standard	No push button (PX)	Push button (PM1) ⁸	No push button (PX)	Push button (PM1) — required
	Optional	Push button (PM1)	No push button (PX)	Push button (PM1) ⁸	-
Volume Control	Standard	-	No VC (VCX)	No VC (VCX)	No VC (VCX)
	Optional	-	Digital VC (VC3)	Digital VC (VC3)	Digital VC (VC3)
T-Coil ⁵	Standard	No T-coil (TX)	No T-coil (TX)	No T-coil (TX)	-
	Optional	T-coil (TP)	T-coil (TP) ⁸	T-coil (TP) ⁸	-
Magnetic switch function	Standard	MiniControl (DT5)	EasyPhone (DT4) ⁸	EasyPhone (DT4) ⁸	-
	Optional	EasyPhone (DT6)	MiniControl (DT3) No EasyPhone (RX)	No EasyPhone (RX)	-
Wax system	Standard	Cerustop (CS) — required	Cerustop (CS)	Cerustop (CS)	Cerustop (CS)
	Optional	-	Extended rec. tube (ER) Wax Spring (WS) Ext. Tube + Spring (WE) Wax guard not required (X)	Extended rec. tube (ER) Wax Spring (WS) Ext. Tube + Spring (WE) Wax guard not required (X)	Extended rec. tube (ER) Wax Spring (WS) Ext. Tube + Spring (WE) Wax guard not required (X)
Removal line	Standard	Removal line transparent (RF) ⁶	Removal line transparent (RF) ⁶	-	-
	Optional	-	Removal line transparent (RF)	Removal line transparent (RF)	Removal line transparent (RF)
Acrylic/retention options	Optional	-	Canal lock ^{5, 7} Helix lock ^{5, 7} Raised VC Canal bell	Canal lock ^{5, 7} Helix lock ^{5, 7} Raised VC Canal bell	Canal lock ^{5,7} Helix lock ^{5,7} Raised VC Canal bell

- 5 Chargeable option
- 6 Standard for IIC and CIC
- 7 Color will match shell color
- 8 Not available in combination with VC

Titanium Information

Vent Options

AOV = Acoustically Optimized Vent. Phonak will set the correct vent diameter and style in relation to Audiogram/shell geometry/feedback canceler and required low frequency gain. This is the recommended vent type.

AOV-O = Acoustically Optimized Vent-Open. This specific vent is more open and recommended for first time users and clients who are sensitive to occlusion. Only available for Virto M-Titanium.

Titanium FitGuide


Measure the possible insertion depth. The device will be built in accordance with the indicated FitGuide value. If the measurement falls between two numbers, please use the smaller number.

- Side M for devices with M-receiver
- Side P for devices with P-receiver
- Models with SP receiver will be built without FitGuide information

Impression Taking

Recommendations for taking impressions:

- EasyView Otoblock placed past the second bend
- Low viscosity material
- Always fill the complete concha with impression material
- Intertragal notch must be visible 4
- When fitting Titanium, impression length must cover the evaluated FitGuide value



All of our products, including custom products and spare parts, can be ordered online in the Phonak store.

Sonova USA Inc. is not responsible and assumes no liability for any non-Phonak manufactured device or accessory sent by you to Phonak. Please ensure that you only include Phonak devices and accessories herein. Products, options and accessories are subject to change without notice.

Last updated: October 28, 2022