Phonak ComPilot and LG Bluetooth pairing guide

- 1. Charge and turn on the mobile phone and ComPilot.
- 2. Place them next to each other.
- 3. Prepare ComPilot for pairing
- Press and hold the Connect () and Volume + buttons simultaneously for 2 seconds until the Audio indicator starts to rapidly blink blue.
- Start the pairing process on the phone as described below.
- Please consult your phone's user guide if you need more information.

4. Prepare the mobile phone for pairing

Find the connectivity settings of the phone. With most models, the following navigation applies. The **Bold** terms might be different depending on the exact phone model.

Pairing older models

- Select Menu > Tools > Connectivity
 Bluetooth > Settings
- Ensure Bluetooth is turned **On**
- Select Done > Paired devices > Add
- Wait until Phonak ComPilot is found
- Highlight the **ComPilot** in the list then **OK**
- Enter the PIN code 0000 (4 zeros)
- Select OK

Pairing smartphone models (touchscreen)

- Press the Menu key
- Touch Settings > Wireless controls
- Ensure Bluetooth is turned **On**
- Touch Bluetooth settings
- Wait until Phonak ComPilot is found
- Select the Phonak ComPilot in the list of devices
- Enter the PIN code **0000** (4 zeros)
- Select OK

5. End of pairing

- After successful pairing, the ComPilot Audio indicator will stop rapid flashing blue.
- Additionally a headset symbol $\mathbf{\Omega}$ may appear on the main screen of your phone.
- After 2 minutes the ComPilot will automatically exit from pairing mode. If step 4 was not completed before, simply start the pairing mode on ComPilot again as described in step 3.

